



ConnectX[®]-4 VPI

Single/Dual-Port Adapter Cards supporting 100Gb/s with Virtual Protocol Interconnect[®]



ConnectX-4 adapter cards with Virtual Protocol Interconnect (VPI), supporting EDR 100Gb/s InfiniBand and 100Gb/s Ethernet connectivity, provide the highest performance and most flexible solution for high-performance, Web 2.0, Cloud, data analytics, database, and storage platforms.

With the exponential growth of data being shared and stored by applications and social networks, the need for high-speed and high performance compute and storage data centers is skyrocketing.

ConnectX[®]-4 provides exceptional high performance for the most demanding data centers, public and private clouds, Web2.0 and Big Data applications, as well as High-Performance Computing (HPC) and Storage systems, enabling today's corporations to meet the demands of the data explosion.

ConnectX[®]-4 provides an unmatched combination of 100Gb/s bandwidth in a single port, the lowest available latency, and specific hardware offloads, addressing both today's and the next generation's compute and storage data center demands.

100Gb/s Virtual Protocol Interconnect (VPI) Adapter

ConnectX-4 offers the highest throughput VPI adapter, supporting EDR 100Gb/s InfiniBand and 100Gb/s Ethernet and enabling any standard networking, clustering, or storage to operate seamlessly over any converged network leveraging a consolidated software stack.

I/O Virtualization

ConnectX-4 SR-IOV technology provides dedicated adapter resources and guaranteed isolation and protection for virtual machines (VMs) within the

server. I/O virtualization with ConnectX-4 gives data center administrators better server utilization while reducing cost, power, and cable complexity, allowing more Virtual Machines and more tenants on the same hardware.

Overlay Networks

In order to better scale their networks, data center operators often create overlay networks that carry traffic from individual virtual machines over logical tunnels in encapsulated formats such as NVGRE and VXLAN. While this solves network scalability issues, it hides the TCP packet from the hardware offloading engines, placing higher loads on the host CPU. ConnectX-4 effectively addresses this by providing advanced NVGRE and VXLAN hardware offloading engines that encapsulate and de-encapsulate the overlay protocol headers, enabling the traditional offloads to be performed on the encapsulated traffic. With ConnectX-4, data center operators can achieve native performance in the new network architecture.

HPC Environments

ConnectX-4 delivers high bandwidth, low latency, and high computation efficiency for the High Performance Computing clusters. Collective communication is a communication pattern in HPC in which all members of a group of processes participate and share data.

HIGHLIGHTS

BENEFITS

- Highest performing silicon for applications requiring high bandwidth, low latency and high message rate
- World-class cluster, network, and storage performance
- Smart interconnect for x86, ARM, and GPU-based compute and storage platforms
- Cutting-edge performance in virtualized overlay networks (VXLAN and NVGRE)
- Efficient I/O consolidation, lowering data center costs and complexity
- Virtualization acceleration
- Power efficiency
- Scalability to tens-of-thousands of nodes

KEY FEATURES

- EDR 100Gb/s InfiniBand or 100Gb/s Ethernet per port
- 10/20/25/40/50/56/100Gb/s speeds
- 150M messages/second
- Single and dual-port options available
- Erasure Coding offload
- T10-DIF Signature Handover
- Virtual Protocol Interconnect (VPI)
- CPU offloading of transport operations
- Application offloading
- Mellanox PeerDirect[™] communication acceleration
- Hardware offloads for NVGRE and VXLAN encapsulated traffic
- End-to-end QoS and congestion control
- Hardware-based I/O virtualization
- RoHS-R6

CORE-Direct® (Collective Offload Resource Engine) provides advanced capabilities for implementing MPI and SHMEM collective operations. It enhances collective communication scalability and minimizes the CPU overhead for such operations, while providing asynchronous and high-performance collective communication capabilities. It also enhances application scalability by reducing the exposure of the collective communication to the effects of system noise (the bad effect of system activity on running jobs). ConnectX-4 enhances the CORE-Direct™ capabilities by removing the restriction on the data length for which data reductions are supported.

RDMA and RoCE

ConnectX-4, utilizing IBTA RDMA (Remote Data Memory Access) and RoCE (RDMA over Converged Ethernet) technology, delivers low-latency and high-performance over InfiniBand and Ethernet networks. Leveraging data center bridging (DCB) capabilities as well as ConnectX-4 advanced congestion control hardware mechanisms, RoCE provides efficient low-latency RDMA services over Layer 2 and Layer 3 networks.

Mellanox PeerDirect™

PeerDirect™ communication provides high efficiency RDMA access by eliminating unnecessary internal data copies between components on the PCIe bus (for example, from GPU to CPU), and therefore significantly reduces application run time. ConnectX-4 advanced acceleration technology enables higher cluster efficiency and scalability to tens of thousands of nodes.

Storage Acceleration

Storage applications will see improved performance with the higher bandwidth EDR delivers. Moreover, standard block and file access protocols can leverage RoCE and InfiniBand RDMA for high-performance storage access. A consolidated compute and storage network achieves significant cost-performance advantages over multi-fabric networks.

Distributed RAID

ConnectX-4 delivers advanced Erasure Coding offloading capability, enabling distributed RAID (Redundant Array of Inexpensive Disks), a data storage technology that combines multiple disk drive components into a logical unit for the purposes of data redundancy and performance improvement. The

ConnectX-4 family's Reed-Solomon capability introduces redundant block calculations, which, together with RDMA, achieves high performance and reliable storage access.

Signature Handover

ConnectX-4 supports hardware checking of T10 Data Integrity Field / Protection Information (T10-DIF/PI), reducing the CPU overhead and accelerating delivery of data to the application. Signature handover is handled by the adapter on ingress and/or egress packets, reducing the load on the CPU at the Initiator and/or Target machines.

Software Support

All Mellanox adapter cards are supported by Windows, Linux distributions, VMware, FreeBSD, and Citrix XENServer. ConnectX-4 VPI adapters support OpenFabrics-based RDMA protocols and software and are compatible with configuration and management tools from OEMs and operating system vendors.

COMPATIBILITY

PCI EXPRESS INTERFACE

- PCIe Gen 3.0 compliant, 1.1 and 2.0 compatible
- 2.5, 5.0, or 8.0GT/s link rate x16
- Auto-negotiates to
- x16, x8, x4, x2, or x1
- Support for MSI/MSI-X mechanisms

CONNECTIVITY

- Interoperable with InfiniBand or 10/25/40/50/100Gb Ethernet switches
- Passive copper cable with ESD protection
- Powered connectors for optical and active cable support

OPERATING SYSTEMS/DISTRIBUTIONS*

- RHEL/CentOS
- Windows
- FreeBSD
- VMware
- OpenFabrics Enterprise Distribution (OFED)
- OpenFabrics Windows Distribution (WinOF)

*Refer to Dell for current OS/distributions

Ordering Part Number	Description
540-BBOB	ConnectX-4 VPI EDR adapter card, dual-port QSFP, short bracket
540-BBQG	ConnectX-4 VPI EDR adapter card, dual-port QSFP, tall bracket
540-BBOG	ConnectX-4 VPI EDR adapter card, single-port QSFP, short bracket
540-BBQI	ConnectX-4 VPI EDR adapter card, single-port QSFP, tall bracket

FEATURE SUMMARY*

INFINIBAND

- 2 ports EDR / FDR / QDR / DDR / SDR
- IBTA Specification 1.3 compliant
- RDMA, Send/Receive semantics
- Hardware-based congestion control
- 16 million I/O channels
- 256 to 4Kbyte MTU, 2Gbyte messages

ENHANCED FEATURES

- Hardware-based reliable transport
- Collective operations offloads
- Hardware-based reliable multicast
- Extended Reliable Connected transport (XRC)

ETHERNET

- 100GbE / 56GbE / 50GbE / 40GbE / 25GbE / 10GbE / 1GbE
- IEEE 802.3bj, 802.3bm 100 Gigabit Ethernet
- 25G Ethernet Consortium 25, 50 Gigabit Ethernet
- IEEE 802.3ba 40 Gigabit Ethernet
- IEEE 802.3ae 10 Gigabit Ethernet
- IEEE 802.3az Energy Efficient Ethernet
- IEEE 802.3ap based auto-negotiation and KR startup

- IEEE 802.3ad, 802.1AX Link Aggregation
- IEEE 802.1Q, 802.1P VLAN tags and priority
- IEEE 802.1Qau (QCN) – Congestion Notification
- IEEE 802.1Qaz (ETS)
- Jumbo frame support (9.6KB)

OVERLAY NETWORKS

- Stateless offloads for overlay networks and tunneling protocols
- Hardware offload of encapsulation and decapsulation of NVGRE and VXLAN overlay networks

HARDWARE-BASED I/O VIRTUALIZATION

- Single Root IOV
- Multi-function per port
- Address translation and protection
- Multiple queues per virtual machine
- Enhanced QoS for vNICs
- VMware NetQueue support

CPU OFFLOADS

- RDMA over Converged Ethernet (RoCE)
- TCP/UDP/IP stateless offload
- LSO, LRO, checksum offload
- RSS (can be done on encapsulated packet),

TSS, HDS, VLAN insertion / stripping, Receive flow steering

- Intelligent interrupt coalescence

REMOTE BOOT

- Remote boot over InfiniBand
- Remote boot over Ethernet
- Remote boot over iSCSI
- PXI and UEFI

PROTOCOL SUPPORT

- OpenMPI, IBM PE, OSU MPI (MVAPICH/2), Intel MPI,
- Platform MPI, UPC, Mellanox SHMEM
- TCP/UDP, EoIB, IPoIB,
- SRP, iSER, NFS RDMA, SMB Direct
- uDAPL

MANAGEMENT AND CONTROL INTERFACES

- Refer to www.Dell.com for management and control.

* This section describes hardware features and capabilities. Please refer to the driver release notes for feature availability

Mellanox Dell Contacts:

Rob MacDonald
OEM Sales Mgr.
Tel: +(44) 7788-967621
robm@mellanox.com

Ronnie Payne
OEM Business Dev. Mgr.
Tel: (512) 201-3030
ronniep@mellanox.com

Will Stepanov
Technical Sales Rep.
Tel: (512) 966-4993
will@mellanox.com

Denise Cowart
Sr. Sales Manager, OEM Sales
+1 (512) 853-0937
denisec@mellanox.com

General Inquiry:

DellSales@mellanox.com



350 Oakmead Parkway, Suite 100
Sunnyvale, CA 94085
Tel: 408-970-3400 • Fax: 408-970-3403
www.mellanox.com

