



ADAPTER CARDS

ConnectX[®]-2 VPI

Dual-Port adapter with *Virtual Protocol Interconnect*[®] for Dell PowerEdge C6100-series Rack Servers

ConnectX-2 adapter cards with *Virtual Protocol Interconnect* (VPI) supporting InfiniBand and Ethernet connectivity provide the highest performing and most flexible interconnect solution for Enterprise Data Centers, High-Performance Computing, and Embedded environments. Clustered data bases, parallel processing, transactional services and high-performance embedded I/O applications will achieve significant performance improvements resulting in reduced completion time and lower cost per operation. ConnectX-2 with VPI also simplifies network deployment by consolidating cables and enhancing performance in virtualized server environments.

Virtual Protocol Interconnect

VPI-enabled adapters make it possible for Dell PowerEdge C6100-series Rack Servers to operate over any converged network leveraging a consolidated software stack. With auto-sense capability, each ConnectX-2 port can identify and operate on InfiniBand, Ethernet, or Data Center Bridging (DCB) fabrics. FlexBoot™ provides additional flexibility by enabling servers to boot from remote InfiniBand or LAN storage targets. ConnectX-2 with VPI and FlexBoot simplifies I/O system design and makes it easier for IT managers to deploy infrastructure that meets the challenges of a dynamic data center.


World-Class Performance

InfiniBand —ConnectX-2 delivers low latency, high bandwidth, and computing efficiency for performance-driven server and storage clustering applications. Efficient computing is achieved by offloading from the CPU routine activities which allows more processor power for the application. Network protocol processing and data movement overhead such as InfiniBand RDMA and Send/Receive semantics are completed in the adapter without CPU intervention. ConnectX-2 advanced acceleration technology enables higher cluster efficiency and large scalability to tens of thousands of nodes.

RDMA over Converged Ethernet — ConnectX-2 utilizing IBTA RoCE technology delivers similar low-latency and high-performance over Ethernet networks. Leveraging Data Center Bridging capabilities, RoCE provides efficient low latency RDMA services over Layer 2 Ethernet. The RoCE software stack maintains existing and future compatibility with bandwidth and latency sensitive applications. With link-level interoperability in existing Ethernet infrastructure, Network Administrators can leverage existing data center fabric management solutions

TCP/UDP/IP Acceleration — Applications utilizing TCP/UDP/IP transport can achieve industry-leading throughput over InfiniBand or 10GigE. The hardware-based stateless offload engines in ConnectX-2 reduce the CPU overhead of IP packet transport, freeing more processor cycles to work on the application.

I/O Virtualization — ConnectX-2 with Virtual Intelligent Queuing (Virtual-IQ) technology provides dedicated adapter resources and guaranteed isolation and protection for virtual machines (VM) within the server. I/O virtualization with ConnectX-2 gives data center managers better server utilization and LAN and SAN unification while reducing cost, power, and cable complexity.



ConnectX[®]-2

BENEFITS

- One adapter for InfiniBand, 10 Gigabit Ethernet or Data Center Bridging fabrics
- World-class cluster performance
- High-performance networking and storage access
- Guaranteed bandwidth and low-latency services
- Reliable transport
- I/O consolidation
- Virtualization acceleration
- Scales to tens-of-thousands of nodes

KEY FEATURES

- Virtual Protocol Interconnect
- 1us MPI ping latency
- Selectable 10, 20, or 40Gb/s InfiniBand or 10 Gigabit Ethernet per port
- PCI Express 2.0 (up to 5GT/s)
- CPU offload of transport operations
- End-to-end QoS and congestion control
- Hardware-based I/O virtualization
- Fibre Channel encapsulation (FCoIB or FCoE)
- RoHS-R6



Third party information brought to you courtesy of Dell.

Storage Accelerated — A consolidated compute and storage network achieves significant cost-performance advantages over multi-fabric networks. Standard block and file access protocols can leverage InfiniBand RDMA for high-performance storage access. T11 compliant encapsulation (FCoIB or FCoE) with full hardware offloads simplifies the storage network while keeping existing Fibre Channel targets.

Software Support

All Mellanox adapter cards are supported by a full suite of drivers for Microsoft Windows, Linux distributions, VMware, and Citrix XENServer. ConnectX-2 VPI adapters support OpenFabrics-based RDMA protocols and software. Stateless offload are fully interoperable with standard TCP/UDP/IP stacks. ConnectX-2 VPI adapters are compatible with configuration and management tools from OEMs and operating system vendors.



FEATURE SUMMARY

INFINIBAND

- IBTA Specification 1.2.1 compliant
- RDMA, Send/Receive semantics
- Hardware-based congestion control
- Atomic operations
- 16 million I/O channels
- 256 to 4Kbyte MTU, 1Gbyte messages
- 9 virtual lanes: 8 data + 1 management

ENHANCED INFINIBAND

- Hardware-based reliable transport
- GPU communication acceleration
- Hardware-based reliable multicast
- Extended Reliable Connected transport
- Enhanced Atomic operations

ETHERNET

- IEEE 802.3ae 10 Gigabit Ethernet
- IEEE 802.3ad Link Aggregation and Failover
- IEEE 802.1Q, 1p VLAN tags and priority
- IEEE P802.1au D2.0 Congestion Notification
- IEEE P802.1az D0.2 ETS
- IEEE P802.1bb D1.0 Priority-based Flow Control
- Jumbo frame support (10KB)
- 128 MAC/VLAN addresses per port

HARDWARE-BASED I/O VIRTUALIZATION

- Single Root IOV
- Address translation and protection
- Dedicated adapter resources
- Multiple queues per virtual machine
- Enhanced QoS for vNICs
- VMware NetQueue support

ADDITIONAL CPU OFFLOADS

- RDMA over Converged Ethernet
- TCP/UDP/IP stateless offload
- Intelligent interrupt coalescence

STORAGE SUPPORT

- FCoE, FCoIB

FLEXBOOT™ TECHNOLOGY

- Remote boot over InfiniBand
- Remote boot over Ethernet
- Remote boot over iSCSI

COMPATIBILITY

PCI EXPRESS INTERFACE

- PCIe Base 2.0 compliant, 1.1 compatible
- 2.5GT/s or 5.0GT/s link rate x8 (20+20Gb/s or 40+40Gb/s bidirectional bandwidth)
- Auto-negotiates to x8, x4, x2, or x1
- Fits Dell PowerEdge C6100 Rack servers
- Support for MSI/MSI-X mechanisms

CONNECTIVITY

- Interoperable with InfiniBand or 10GigE switches
- QSFP connectors
- 20m+ (10Gb/s), 10m+ (20Gb/s) or 7m+ (40Gb/s InfiniBand or 10GigE) of passive copper cable
- External optical media adapter and active cable support
- QSFP to SFP+ connectivity through QSA module

MANAGEMENT AND TOOLS

InfiniBand

- OpenSM
- Interoperable with third-party subnet managers
- Firmware and debug tools (MFT, IBDIAG)

Ethernet

- MIB, MIB-II, MIB-II Extensions, RMON, RMON 2
- Configuration and diagnostic tools

OPERATING SYSTEMS/DISTRIBUTIONS

- Novell SLES, Red Hat Enterprise Linux (RHEL), Fedora, and other Linux distributions
- Microsoft Windows Server 2003/2008/CCS 2003
- OpenFabrics Enterprise Distribution (OFED)
- OpenFabrics Windows Distribution (WinOF)
- VMware ESX Server 3.5/vSphere 4.0

PROTOCOL SUPPORT

- Open MPI, OSU MVA PICH, Intel MPI, MS MPI, Platform MPI
- TCP/UDP, EoIB, IPoIB, SDP, RDS
- SRP, iSER, NFS RDMA, FCoIB, FCoE
- uDAPL



The information contained in this document, including all instructions, cautions, and regulatory approvals and certifications, is provided by Mellanox and has not been independently verified or tested by Dell. Dell cannot be responsible for damage caused as a result of either following or failing to follow these instructions. All statements or claims regarding the properties, capabilities, speeds or qualifications of the part referenced in this document are made by Mellanox and not by Dell. Dell specifically disclaims knowledge of the accuracy, completeness or substantiation for any such statements. All questions or comments relating to such statements or claims should be directed to Mellanox. Visit www.dell.com for more information.



350 Oakmead Parkway, Suite 100, Sunnyvale, CA 94085
Tel: 408-970-3400 • Fax: 408-970-3403
www.mellanox.com

© Copyright 2010. Mellanox Technologies. All rights reserved.

Mellanox, BridgeX, ConnectX, InfiniBlast, InfiniBridge, InfiniHost, InfiniRISC, InfiniScale, InfiniPCI, and Virtual Protocol Interconnect are registered trademarks of Mellanox Technologies, Ltd. CORE-Direct, FabricIT, and PhyX are trademarks of Mellanox Technologies, Ltd. All other trademarks are property of their respective owners.