



SX6025

36-port Non-blocking Unmanaged 56Gb/s InfiniBand SDN Switch System

SX6025 switch system provides the highest performing fabric solution in a 1U form factor by delivering up to 4Tb/s of non-blocking bandwidth with 200ns port-to-port latency.

Scaling-Out Data Centers with Fourteen Data Rate (FDR) InfiniBand

Faster servers based on PCIe 3.0, combined with high-performance storage and applications that use increasingly complex computations, are causing data bandwidth requirements to spiral upward. As servers are deployed with next generation processors, High-Performance Computing (HPC) environments and Enterprise Data Centers (EDC) will need every last bit of bandwidth delivered with Mellanox's next generation of FDR InfiniBand high-speed smart switches.

FDR

FDR InfiniBand technology moves from 8b/10b encoding a more efficient 64/66 encoding while increasing the per lane signaling rate to 14Gb/s. Mellanox end-to-end systems can also take advantage of the efficiency of 64/66 encoding using Mellanox FDR 10 supporting 20% more bandwidth over QDR using the same cables/connectors designed for 40GbE.

Sustained Network Performance

Built with Mellanox's latest SwitchX[®] InfiniBand switch device, the SX6025 provides up to thirty-six 56Gb/s full bi-directional bandwidth per port. These stand-alone switches are an ideal choice for top-of-rack leaf connectivity or for building small to extremely large sized clusters.

Why Software Defined Network (SDN)?

Data center networks have become exceedingly complex. IT managers cannot optimize the networks for their applications leading to

high CAPEX/OPEX, low ROI and IT headaches. Mellanox InfiniBand SDN Switches ensure separation between control and data planes. InfiniBand enables centralized management and view of network. Programmability of the network by external applications and enable cost effective, simple and flat interconnect infrastructure.

Smart Switches for Smart Clusters

The SX6025 enables efficient computing with features such as static routing, adaptive routing, and congestion control. These features ensure the maximum effective fabric bandwidth by eliminating congestion hot spots. Whether used for parallel computation or as a converged fabric, the SX6000 family of switches provides the industry's best traffic-carrying capacity, making it easy to build clusters that can scale-out to thousands-of-nodes.

The SX6025 supports reversible airflow making the design fit into data centers with different thermal designs. Optional redundant and hot swappable power supplies and fans provide high availability for both High-Performance and Enterprise Data Center applications.

Building Efficient Clusters & Grids

The SX6025 is the industry's most cost-effective building block for deploying high performance clusters and data centers. Whether looking at price-to-performance or energy-to-performance, the SX6025 offers superior performance, power and scale reducing capital and operating expenses providing the best return-on-investment.



HIGHLIGHTS

BENEFITS

- Software Defined Network (SDN) support
- Industry-leading, switch platform in performance, power, and density
- Designed for energy and cost savings
- Low latency
- Maximizes performance by removing fabric congestions

KEY FEATURES

- 36 FDR (56Gb/s) ports in a 1U switch
- Up to 4Tb/s aggregate switching capacity
- Compliant with IBTA 1.2.1 and 1.3
- FDR/FDR10 support for Forward Error Correction (FEC)
- Port mirroring
- Optional redundant power supplies and fan drawers
- RoHS-6 complaint



HARDWARE

MELLANOX SX6025

- 19" rack mountable chassis, 1U with optional redundant power supplies and Fan units
- 36 QSFP non blocking ports with aggregate throughput up to 4.032 Tb/s (FDR)
- Port-to-port latency 200ns

SWITCH SPECIFICATIONS

- Compliant with IBTA 1.21 and 1.3
- 9 virtual lanes: 8 data + 1 management
- 256 to 4Kbyte MTU
- Adaptive Routing**
- Congestion control
- Port Mirroring
- 4X48K entry linear forwarding data base

MANAGEMENT PORTS

- I²C (RJ45)
- System reset button

CONNECTORS AND CABLING

- QSFP connectors
- Passive copper or active fiber cables
- Fiber media adapters

INDICATORS

- Per port status LED Link, Activity
- System status LEDs: System, fans, power supplies
- Port Error LED
- Unit ID LED**

PHYSICAL CHARACTERISTICS

- Dimensions: (1.72"H X 16.84"W X 24.7"D)
- Weight: 20.5 Lbs (9.3 Kgs)

POWER SUPPLY

- Dual redundant slots
- Hot plug operation
- Input range: 100 - 240VAC
- Frequency: 50-60Hz, single phase AC

POWER CONSUMPTION

FDR - Typical power consumption:

- Passive cable - 113W
- Active cable - 217W

COOLING

- Front-to-rear or rear-to-front cooling option
- Hot-swappable fan unit

COMPLIANCE

SAFETY

- US/Canada: cTUVus
- EU: IEC60950
- International: CB
- Russia: GOST-R
- Argentina: S-mark

POWER SUPPLIES

- China CCC
- Korea KCC

EMC (EMISSIONS)

- USA: FCC, Class A
- Canada: ICES, Class A
- EU: EN55022, Class A
- EU: EN55024, Class A
- EU: EN61000-3-2, Class A
- EU: EN61000-3-3, Class A
- Japan: VCCI, Class A
- Australia: C-TICK
- Brazil : ANATEL
- Taiwan : BSMI

ENVIRONMENTAL

- EU: IEC 60068-2-64: Random Vibration
- EU: IEC 60068-2-29: Shocks, Type I / II
- EU: IEC 60068-2-32: Fall Test

ACOUSTIC

- ISO 7779
- ETS 300 753

OPERATING CONDITIONS

- Operating 0°C to 45°C
- Humidity: Operating 10% to 85% non condensing
- Altitude: Operating -60 to 3200m

OTHERS

- RoHS-6 compliant
- Rack-mountable, 1U
- 1-year warranty

Ordering Part Number	Description
MSX6025F-1SFS	SwitchX [®] -2 based 36-port QSFP FDR 1U Externally Managed InfiniBand switch system with a non-blocking switching capacity of 4Tb/s. 1PS, Standard depth, Forward airflow*, RoHS-6
MSX6025T-1SFS	SwitchX [®] -2 based 36-port QSFP FDR10 1U Externally Managed InfiniBand switch system with a non-blocking switching capacity of 2.9Tb/s. 1PS, Standard depth, Forward airflow*, RoHS-6
MSX60-PF	300W Power supply with power supply side to connector side air flow for MSX60xx and MSX10xx series switch systems
MSX60-PR	300W Power supply with connector side to power supply side air flow for MSX60xx and MSX10xx series switch systems

* Forward airflow is connector side outlet. Reverse airflow in connector side inlet; available in short depth

**Available in future release

Mellanox Dell Contacts:

Rob MacDonald
 OEM Sales Mgr.
 Tel: +(44) 7788-967621
 robm@mellanox.com

Ronnie Payne
 OEM Business Development Mgr.
 Tel: (512) 201-3030
 ronniep@mellanox.com

General Inquiry:

DellSales@mellanox.com



The information contained in this document, including all instructions, cautions, and regulatory approvals and certifications, is provided by Mellanox and has not been independently verified or tested by Dell. Dell cannot be responsible for damage caused as a result of either following or failing to follow these instructions. All statements or claims regarding the properties, capabilities, speeds or qualifications of the part referenced in this document are made by Mellanox and not by Dell. Dell specifically disclaims knowledge of the accuracy, completeness or substantiation for any such statements. All questions or comments relating to such statements or claims should be directed to Mellanox. Visit www.dell.com for more information. Dell is a registered trademark of Dell Inc.



350 Oakmead Parkway, Suite 100, Sunnyvale, CA 94085
 Tel: 408-970-3400 • Fax: 408-970-3403
www.mellanox.com