



Connect-IB[®] InfiniBand Adapter Cards



Single/Dual-Port InfiniBand Host Channel Adapter Cards

Connect-IB adapter cards provide the highest performing and most scalable interconnect solution for server and storage systems. High-Performance Computing, Web 2.0, Cloud, Big Data, Financial Services, Virtualized Data Centers and Storage applications will achieve significant performance improvements resulting in reduced completion time and lower cost per operation.

WORLD CLASS PERFORMANCE

Connect-IB delivers leading performance with maximum bandwidth, low latency, and computing efficiency for performance-driven server and storage applications. Maximum bandwidth is delivered across PCI Express 3.0 x16 and two ports of FDR InfiniBand, supplying more than 100Gb/s of throughput together with consistent low latency across all CPU cores. Connect-IB also enables PCI Express 2.0 x16 systems to take full advantage of FDR, delivering at least twice the bandwidth of existing PCIe 2.0 solutions.

Connect-IB offloads the CPU protocol processing and the data movement from the CPU to the interconnect, maximizing the CPU efficiency and accelerate parallel and data-intensive application performance. Connect-IB supports new data operations including noncontinuous memory transfers which eliminate unnecessary data copy operations and CPU overhead. Additional application acceleration is achieved with a 4X improvement in message rate compared with previous generations of InfiniBand cards.

UNLIMITED SCALABILITY

The next level of scalability and performance requires a new generation of data and application accelerations. Mellanox Messaging (MXM) and Fabric Collective Accelerator (FCA) utilizing CORE-Direct[®] technology accelerate MPI and PGAS communication performance, taking full advantage of Connect-IB enhanced capabilities. Furthermore, Connect-IB introduces an innovative transport service, Dynamic Transport, to ensure unlimited scalability for clustering of servers and storage systems.

HIGH PERFORMANCE STORAGE

Storage nodes will see improved performance with the higher bandwidth FDR delivers, and standard block and file access protocols can leverage InfiniBand RDMA for even better performance. Connect-IB also supports hardware checking of T10 Data Integrity Field / Protection Information (DIF/PI) and other signature types, reducing the CPU overhead and accelerating the data to the application. Signature translation and handover are also done by the adapter, further reducing the load on the CPU. Consolidating compute and storage over FDR InfiniBand with Connect-IB achieves superior performance while reducing data center costs and complexities.

HIGHLIGHTS

BENEFITS

- World-class cluster, network, and storage performance
- Guaranteed bandwidth and low-latency services
- I/O consolidation
- Virtualization acceleration
- Power efficient
- Scales to tens-of-thousands of nodes

FEATURES

- Greater than 100Gb/s over InfiniBand
- Greater than 130M messages/sec
- 1us MPI ping latency
- PCI Express 3.0 x16
- CPU offload of transport operations
- Application offload
- GPU communication acceleration
- End-to-end internal data protection
- End-to-end QoS and congestion control
- Hardware-based I/O virtualization
- RoHS-R6

SOFTWARE SUPPORT

All Mellanox adapter cards are supported by all Linux distributions. Connect-IB adapters support OpenFabrics-based RDMA protocols and software, and are compatible with configuration and management tools from OEMs and operating system vendors.

MELLANOX ADVANTAGE

Mellanox Technologies is a leading supplier of end-to-end servers and storage interconnect solutions to optimize high performance computing performance and efficiency. Mellanox InfiniBand adapters, switches, and software are powering the largest supercomputers in the world. For the best in server and storage performance and scalability with the lowest TCO, Mellanox interconnect products are the solution.

FEATURES

InfiniBand

- IBTA Specification 1.2.1 compliant
- FDR 56Gb/s InfiniBand
- Hardware-based congestion control
- 16 million I/O channels
- 256 to 4Kbyte MTU, 1Gbyte messages

Enhanced Features

- Hardware-based reliable transport
- Extended Reliable Connected transport
- Dynamically Connected transport service
- Signature-protected control objects
- Collective operations offloads

- GPU communication acceleration
- Enhanced Atomic operations

Storage Support

- T10-compliant DIF/PI support
- Hardware-based data signature handovers

FlexBoot™ Technology

- Remote boot over InfiniBand

Hardware-Based I/O Virtualization

- Single Root IOV**
- Up to 16 physical functions, 256 virtual functions
- Address translation and protection

- Dedicated adapter resources
- Multiple queues per virtual machine
- Enhanced QoS for vNICs and vHCAs
- VMware NetQueue support

Protocol Support

- OpenMPI, IBM PE, Intel MPI, OSU MPI (MVAPICH/2), Platforms MPI, UPC, Mellanox SHMEM
- TCP/UDP, IPoIB, RDS
- SRP, iSER, NFS RDMA, SMB Direct
- uDAPL

COMPATIBILITY

PCI Express Interface

- PCI Express 2.0 or 3.0 compliant
- Auto-negotiates to x16, x8, x4, or x1
- Support for MSI-X mechanisms

Operating Systems/Distributions*

- Novell SLES, Red Hat Enterprise Linux (RHEL), and other Linux distributions
- OpenFabrics Enterprise Distribution (OFED)

Connectivity

- Interoperable with InfiniBand switches
- Passive copper cable with ESD protection
- Powered connectors for optical and active cable support

* This section describes hardware features and capabilities. Please refer to the driver and firmware release notes for feature availability.

**Future support.

Table 1 - Part Numbers and Descriptions

OPN	InfiniBand Ports	PCI Express
MCB191A-FCAT	Single FDR 56Gb/s	3.0 x8
MCB192A-FCAT	Dual FDR 56Gb/s	3.0 x8
MCB193A-FCAT	Single FDR 56Gb/s	3.0 x16
MCB194A-FCAT	Dual FDR 56Gb/s	3.0 x16

NOTE: All tall-bracket adapters are shipped with the tall bracket mounted and a short bracket as an accessory.



350 Oakmead Parkway, Suite 100, Sunnyvale, CA 94085
 Tel: 408-970-3400 • Fax: 408-970-3403
www.mellanox.com