

TX6240

RDMA Long-Haul Solutions to the Metro

The MetroX[™] TX6240 extends Mellanox's RDMA solutions from a single-location data center network to distances up to 40km for campus and metro applications.

Scaling-Out Data Centers with MetroX

Data centers, compute clusters and supercomputers are overwhelmed by unprecedented growth in data volume, fueled by strong application and technology trends.

While Mellanox products have been traditionally deployed for their high-performance interconnect benefits within the data center, Mellanox's MetroX solutions, implementing long-haul RDMA, enable connections between data centers deployed across multiple geographically distributed sites, extending the same world-leading interconnect benefits of Mellanox switches beyond local data centers and storage clusters.

Mellanox's MetroX is the perfect cost-effective, low power, easily managed and scalable solution that enables today's data centers and storage to run over local and distributed fabrics, managed as a single unified network infrastructure.

Long-Haul RDMA

The TX6240 system can transfer two QSFP+ 40Gb/s ports to distances of up to 40km. The solution enables aggregate data and storage networking over a single, consolidated fabric. The long-haul RDMA technology guarantees high-performance, high-volume data sharing between distant sites, enabling existing data centers expansion, disaster recovery, data mirroring and campus connectivity.

MetroX Package

The TX6240 solution package is a full bundle including all cables and WDM modules interconnect to support the long distance leaving standard QSFP and LC connector as the user interface.

The bundle includes:

- MEX6240 - 40km long haul 40Gb/s system, a DWDM transponder running standard ITU-T G.694.1 C band wavelength to run on carrier infrastructure.
- 4 X 40km WDM (colored) SFP+
- 4 X SR SFP+ and SR4 QSFP module

40Gb/s Across Metro, 56Gb/s Locally

MetroX 2U bundle latency is 800ns, where each kilometer of transmission across fiber glass adds 5 microseconds of latency.

MetroX ports support Mellanox's VPI technology, which enables any standard networking, storage or management protocol to seamlessly operate over InfiniBand or Ethernet networks.

Optional integrated EDFAs are available (different OPN) to gain booster of +10dB to +22dB and Preamp of +18 dB to overcome noisy fabric.




HIGHLIGHTS

BENEFITS

- Extends RDMA networks up to a 40km radius over dark fiber
- Low cost, low power, long-haul solution over InfiniBand and Ethernet fabrics
- Simple management

KEY FEATURES

- 2 Long haul (40Gb/s) ports in a 2U system
- Up to 80Gb/s long-haul aggregate data
- 2 Downlink (56Gb/s) VPI ports
- Compliant with IBTA 1.2.1 and 1.3
- Supports full C-Band Tunable DWDM Line sides (SFP+)
- Optional integrated EDFAs
- Redundant power supplies and fan drawers

SPECIFICATIONS

MELLANOX TX6240

- 19" rack mountable chassis, 2U with redundant power supplies and Fan units
- 2 Downlink QSFP non blocking ports with aggregate data throughput up to 112Gb/s
- 2 Uplink QSFP non-blocking ports with aggregate data throughput up to 80Gb/s

LONG HAUL SPECIFICATIONS

- Compliant with IBTA 1.2.1 and 1.3
- 2 Virtual Lanes: 1 data + 1 management
- 4X48K entry linear forwarding data base

MANAGEMENT PORTS

- Dual 100/1000 Ethernet ports
- RS232 port over DB9
- USB port

DEVICE MANAGEMENT

- CLI or SNMP

FABRIC MANAGEMENT

- On-board SM for fabrics up to 648 nodes
- Unified Fabric Manager (UFM™) Agent*

CONNECTORS AND CABLING

- QSFP connectors
- Passive copper or active fiber cables
- Fiber media adapters

INDICATORS

- Per port status LED Link, Activity
- System status LEDs: System, fans, power supplies
- Port Error LED
- Unit ID LED*

PHYSICAL CHARACTERISTICS

MTX6240:

- Dimensions: 1.72"H x 16.84"W x 24.7"D
- Weight: 20.5 Lbs (9.3 Kgs)

MEX6240:

- Dimensions: 1.77" H x 17.32" W x 9.05" D
- Weight: 12.1 Lbs (5.5 Kgs)

POWER SUPPLY

- Dual redundant slots
- Input range: 100 - 240VAC
- Frequency: 50-60Hz, single phase AC

COOLING

- Hot-swappable fan unit
- Auto-heat sensing for silent fan operation

POWER CONSUMPTION

- Passive cable - 197W
- Active cable - 291W

WDM LINK

- **Wavelength** - ITU-T G.694.1 Channels, 100GHz spacing, optional tunable SFP+ with 50GHz spacing
- **OSC** -1490nm, 1510nm
- **Optical Output Power** - 1dBm (min) to +2dBm (max)
- **Sensitivity** - 24dBm APD, -14dBm PIN
- **Optical Monitoring** - Tx & Rx power
- **Link Attenuation** - <4dB (Mux + DeMux)
- **Max input power** - 27dBm
- **Insertion loss** - Transmit side 3.8dB
Receiver side 1.2dB

COMPLIANCE

SAFETY

- CB
- cTUVus
- CE
- CU

EMC (EMISSIONS)

- CE
- FCC
- VCCI
- ICES
- RCM

OPERATING CONDITIONS

- Operating 0°C to 45°C,
Non Operating -40°C to 70°C
- Humidity: Operating 5% to 95%
- Altitude: Operating -60 to 2000m

ACOUSTIC

- ISO 7779
- ETS 300 753

OTHERS

- RoHS-6 compliant
- Rack-mountable, 2U
- 1-year warranty

* Available in a future release

Ordering Part Number	Description	Quantity
MTX6240-2F_BL	MetroX™ 40km WDM loss less long haul 40G system bundle, 2 long-haul QSFP+ ports, PSU side to connector side airflow, RoHS6	
BOM includes:		
MTDX6240-2SFS	MetroX™ 40km long haul 40G FRU system, 2 long-haul QSFP+ ports, 2 Power Supplies, Standard depth, Managed, PSU side to connector side airflow, Rail Kit and RoHS6	1
MEX6200-2B	40km WDM FRU box part of TX6240, LC connector, 2 Power Supplies, Short depth, Managed, Rail Kit and RoHS6	1
MC2210411-SR4L	Mellanox® optical module, 40Gb/s, QSFP, MPO, 850nm, up to 30m	1
MC6709309-005	Mellanox® passive fiber hybrid cable, MPO to 8xLC, 5m	1
MFM1T02A-SR	Mellanox® optical module, 10GbE SFP+, LC-LC, 850nm, SR up to 300m	4
UL-SFP+-D-S-CH28	Optical module, 10GbE SFP+, LC-LC, DWDM C-Band, 40km CH#28 up to CH#31	4
UL-SFP+-D-S-CH31		



350 Oakmead Parkway, Suite 100, Sunnyvale, CA 94085
Tel: 408-970-3400 • Fax: 408-970-3403
www.mellanox.com

© Copyright 2015, Mellanox Technologies. All rights reserved.

Mellanox, BridgeX, ConnectX, CORE-Direct, InfiniBridge, InfiniHost, InfiniScale, MLNX-OS, PhyX, SwitchX, Virtual Protocol Interconnect and Voltaire are registered trademarks of Mellanox Technologies, Ltd. Connect-IB, CoolBox, FabricIT, Mellanox Federal Systems, Mellanox Software Defined Storage, MetroX, MetroDX, Mellanox Open Ethernet, Open Ethernet, ScalableHPC, Unbreakable-Link, UFM and Unified Fabric Manager are trademarks of Mellanox Technologies, Ltd. All other trademarks are property of their respective owners.