

Mellanox ConnectX-4/ ConnectX-4 Lx Plugin for RedHat OpenStack Platform 10

Release Notes

Rev 1.0

NOTE:

THIS HARDWARE, SOFTWARE OR TEST SUITE PRODUCT (“PRODUCT(S)”) AND ITS RELATED DOCUMENTATION ARE PROVIDED BY MELLANOX TECHNOLOGIES “AS-IS” WITH ALL FAULTS OF ANY KIND AND SOLELY FOR THE PURPOSE OF AIDING THE CUSTOMER IN TESTING APPLICATIONS THAT USE THE PRODUCTS IN DESIGNATED SOLUTIONS. THE CUSTOMER’S MANUFACTURING TEST ENVIRONMENT HAS NOT MET THE STANDARDS SET BY MELLANOX TECHNOLOGIES TO FULLY QUALIFY THE PRODUCT(S) AND/OR THE SYSTEM USING IT. THEREFORE, MELLANOX TECHNOLOGIES CANNOT AND DOES NOT GUARANTEE OR WARRANT THAT THE PRODUCTS WILL OPERATE WITH THE HIGHEST QUALITY. ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT ARE DISCLAIMED. IN NO EVENT SHALL MELLANOX BE LIABLE TO CUSTOMER OR ANY THIRD PARTIES FOR ANY DIRECT, INDIRECT, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES OF ANY KIND (INCLUDING, BUT NOT LIMITED TO, PAYMENT FOR PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY FROM THE USE OF THE PRODUCT(S) AND RELATED DOCUMENTATION EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.



Mellanox Technologies
350 Oakmead Parkway Suite 100
Sunnyvale, CA 94085
U.S.A.
www.mellanox.com
Tel: (408) 970-3400
Fax: (408) 970-3403

© Copyright 2017. Mellanox Technologies Ltd. All Rights Reserved.

Mellanox®, Mellanox logo, Accelio®, BridgeX®, CloudX logo, CompustorX®, Connect-IB®, ConnectX®, CoolBox®, CORE-Direct®, EZchip®, EZchip logo, EZappliance®, EZdesign®, EZdriver®, EZsystem®, GPUDirect®, InfiniHost®, InfiniBridge®, InfiniScale®, Kotura®, Kotura logo, Mellanox CloudRack®, Mellanox CloudXMellanox®, Mellanox Federal Systems®, Mellanox HostDirect®, Mellanox Multi-Host®, Mellanox Open Ethernet®, Mellanox OpenCloud®, Mellanox OpenCloud Logo®, Mellanox PeerDirect®, Mellanox ScalableHPC®, Mellanox StorageX®, Mellanox TuneX®, Mellanox Connect Accelerate Outperform logo, Mellanox Virtual Modular Switch®, MetroDX®, MetroX®, MLNX-OS®, NP-1c®, NP-2®, NP-3®, Open Ethernet logo, PhyX®, PlatformX®, PSIPHY®, SiPhy®, StoreX®, SwitchX®, Tiler®, Tiler logo, TestX®, TuneX®, The Generation of Open Ethernet logo, UFM®, Unbreakable Link®, Virtual Protocol Interconnect®, Voltaire® and Voltaire logo are registered trademarks of Mellanox Technologies, Ltd.

All other trademarks are property of their respective owners.

For the most updated list of Mellanox trademarks, visit <http://www.mellanox.com/page/trademarks>

Table of Contents

Document Revision History	5
1 Overview	6
1.1 System Requirements	6
1.2 Supported Guest Operating Systems.....	6
1.3 Supported Network Adapter Cards.....	7
1.3.1 Firmware Versions	7
1.4 Management and Driver Software.....	7
2 Key Features	8
3 Product Related Documentation	9

List of Tables

Table 1: Document Revision History	5
Table 2: Undercloud Node Requirements.....	6
Table 3: Overcloud Node Requirements	6
Table 4: Supported Guest Operating Systems	6
Table 5: Supported Network Adapter Cards	7
Table 6: Firmware Versions.....	7
Table 7: Product Related Documentation.....	9

Document Revision History

Table 1: Document Revision History

Revision	Date	Description
1.0	May 4 th , 2017	Initial version of this document.

1 Overview

These are the Release Notes for Mellanox ConnectX-4 and ConnectX-4 Lx Plugin for RedHat OpenStack Platform 10.

1.1 System Requirements

The system requirements are detailed in the following tables:

Table 2: Undercloud Node Requirements

Platform	Type and Version
OS	Red Hat Enterprise Linux 7.3 or later (vanilla)
CPU	An 8-core 64-bit x86 processor with support for the Intel 64 or AMD64 CPU extensions.
Memory	A minimum of 16 GB of RAM.
Disk Space	A minimum of 40 GB of available disk space on the root disk. Make sure to leave at least 10 GB free space before attempting an Overcloud deployment or update. This free space accommodates image conversion and caching during the node provisioning process.
Networking	A minimum of 2 x 1 Gbps Network Interface Cards. However, it is recommended to use a 10 Gbps interface for Provisioning network traffic, especially if provisioning many nodes in your Overcloud environment.

Table 3: Overcloud Node Requirements

	Controller	Compute	Storage
Standalone basic Scenario	1	1	1
High-availability basic scenario	3	1	1

1.2 Supported Guest Operating Systems

The following are the supported Guest OSes:

Table 4: Supported Guest Operating Systems

OS	version
RHEL	7.x
Centos	7.x
Ubuntu	14.04

1.3 Supported Network Adapter Cards

Mellanox ConnectX-4 and ConnectX-4 Lx Plugin for RedHat OpenStack Platform 10 supports the following Mellanox network adapter cards:

Table 5: Supported Network Adapter Cards

NICs	Supported Protocols	Supported Link Speeds
ConnectX®-4	Ethernet	10, 25, 40, 50 and 100 Gb/s
ConnectX®-4 Lx	Ethernet	10, 25, 40 and 50Gb/s

1.3.1 Firmware Versions

Mellanox ConnectX-4 and ConnectX-4 Lx Plugin for RedHat OpenStack Platform 10 provides the following firmware for Mellanox NICs:

Table 6: Firmware Versions

NICs	Recommended Firmware Rev.
ConnectX-4	12.18.2000
ConnectX-4 Lx	14.18.2000

1.4 Management and Driver Software

Software	Supported Versions
MLNX_OFED	v4.0-2.0.0.1

2 Key Features

The Mellanox Redhat Openstack plugin can configure Mellanox ConnectX-4/ConnectX-4 Lx network adapters to accelerate the performance of compute and storage traffic which includes the following main features:

- Support ConnectX-4 and ConnectX-4 Lx adapters (Ethernet only)
- iSER
- SR-IOV/ParaVirtualization (PV)
- OFED 4.0-2.0.0.1
- VXLAN Offloading
- Active-backup Bonding support over network interfaces.
- Auto-generates the basic network interfaces topology for os-net-config

3 Product Related Documentation

Table 7: Product Related Documentation

Document Title	Document Number
Mellanox ConnectX-4/ConnectX-4 Lx Redhat OSP 10 Plugin User Manual	MLNX-15-52350
Mellanox ConnectX-4/ConnectX-4 Lx Redhat OSP 10 Plugin Release Notes	N/A
Redhat OSP 10 Documentation	-