

Transport Layer: ConnectX-2 EN with RoE uses the InfiniBand transport layer, as defined in the IBTA RoCE specification. The adaptation from InfiniBand data link to Ethernet data link is straight forward because the InfiniBand transport layer was designed ground up to be data link layer agnostic. The InfiniBand transport layer expects certain services from the data link layer related to lossless delivery of packets, and these are delivered by a PFC enabled Ethernet data link layer. ConnectX-2 EN with RoE inherits a rich set of transport services beyond those required to support OFA verbs including connected and unconnected modes, reliable and unreliable services. Built on top of these services is a full set of verbs-defined operations including kernel bypass, send/receive, RDMA read/write, and atomic operations.

Network Layer: ConnectX-2 EN with RoE relies on the InfiniBand defined GRH (Global Route Header) based Network Layer. When necessary, ConnectX-2 with RoE requires InfiniBand GRH-based network layer functions. The GRH carries GID (Global Identifier) which is equivalent to IPv6 addressing and can be adapted to IPv4 addressing.

Data Link Layer: At the data link layer level, standard layer 2 Ethernet services are needed, and 802.1bb Priority flow control (PFC) or 802.3x Pause at a minimum to ensure lossless packet delivery. 802.1au congestion notification is desirable but not mandatory unless server to server or server to storage connectivity fabrics are oversubscribed and are prone to congestions. L2 Addressing is based on source and destination MAC addresses. The 802.1Q header priority field alongside 802.1az (ETS) and other Ethernet practices provide a way to implement of QoS. Finally, an IEEE assigned Ethertype is used to indicate that the packet is of type RoCE. The following table summarizes how Ethernet layer 2 header fields are mapped to functions provided by the InfiniBand layer 2 header fields to enable seamless operation of the InfiniBand transport layer over Ethernet data link layer.

Function	InfiniBand L2 Header Field	Ethernet L2 Header Field
Addressing	SLID and DLID	SMAC and DMAC
Priority Queues	Service Level (SL)	802.1Q header priority
Partitioning or VLAN	Partition Key (P-Key)	802.1Q header VLAN ID
Congestion notification	IBTA defined FECN and BECN	802.1Qau QCN

Converged Traffic: A RoCE packet is identified by an Ethertype number in the L2 header. This allows differentiation among different packet types to occur low in the stack and allows different types of Ethernet traffic, including RDMA traffic to simultaneously co-exist on a single physical Ethernet wire. ConnectX-2 EN with RoE uses linear look up on the destination queue pair number (DQPN) in the transport header to de-multiplex traffic into queue pairs.

Management: ConnectX-2 EN with RoE does not require an SM (InfiniBand subnet manager), and can operate using standard Ethernet network management practices for L2 address assignments, L2 topology discovery, and switch filtering data base (FDB) configuration. For example spanning tree and learning can be used. QoS management for RoCEE can be accomplished using Ethernet management practices for 802.1Qaz (ETS). For congestion management features RoCEE relies on 802.1au congestion management features in Ethernet. PFC priority configuration and negotiation with PFC-capable switches can be done statically using VLANs (associating RDMA traffic to VLANs in hosts and assigning high PFC priority to those VLANs in switches) or dynamically using DCB exchange protocols between the NIC and the switch. ConnectX-2 EN with RoE supports both modes of PFC configuration. Finally, performance monitoring, baseboard and device management can be done by using standard SNMP/RMON MIBs.

The following table summarizes how network management characteristics expected by the InfiniBand transport layer and applications using the InfiniBand transport layer can be seamlessly delivered over Ethernet using standard Ethernet management practices and eliminating the need for the InfiniBand Subnet manager. Data center IT managers can continue to use their familiar Ethernet-based manage-

ment tools making deployment of ConnectX-2 EN with RoE in the data center easy like deployment of any other Ethernet-based technology.

Management Feature Required by IB Transport Layer and Apps using IB Transport Layer	How InfiniBand delivers them in the InfiniBand subnet	How Ethernet (and DCB) delivers them using standard Ethernet management practices
L2 address assignment	Subnet Manager L2 address assignment	Fixed assigned L2 address or other Ethernet mechanisms
L2 topology discovery and switch FDB configuration	Subnet Manager topology discovery using direct routed subnet management packets (SMP). Subnet Manager path computation and path distribution	Spanning Tree and Learning mechanisms. Also IETF Transparent Interconnection of Lots of Links (TRILL) when available and other eth practices
Address resolution	SA based path resolution	Address Resolution Protocol (ARP) or direct mapping
QoS	QoS Manager extension to Subnet Manager	Standard Ethernet QoS management practices. Local API to access fabric policy settings
Congestion management	Congestion Manager for IB	802.1Qau congestion management features
Performance management	IB Performance Manager	SNMP/RMON MIBS
Device/baseboard management	IB Baseboard Manager	SNMP/RMON MIBS

ConnectX-2 EN with RoE adapters based on the IBTA RoCE specification are available today from Mellanox Technologies and have been demonstrated to deliver end to end application level latencies of as low as 1.3 microseconds. Mellanox and other industry leaders are collaborating on growing the ecosystem of RoCE-based adapters and independent software vendor applications that capitalize on the benefits of ConnectX-2 EN with RoE. Some examples of target applications are financial services, business intelligence, data warehousing, cloud computing and Web 2.0.

1.2 ConnectX-2 EN with RoE Advantages

Based on the discussion above, it is obvious that ConnectX-2 EN with RoE comes with many advantages and holds the promise to enable widespread deployment of RDMA technologies in mainstream data center applications.

1. ConnectX-2 EN with RoE utilizes advances in Ethernet (DCB) to enable efficient and low cost implementations of RDMA over Ethernet.
2. ConnectX-2 EN RDMA traffic can be classified at the data link layer which is faster and requires less CPU overhead.
3. ConnectX-2 EN with RoE delivers 1.3usec application to application latency, which is 1/10th of other industry standard implementations over Ethernet. Benchmarking with popular financial services applications show more than 60% lower latency applicable to capital market data processing and trade executions.
4. ConnectX-2 EN with RoE supports the entire breath of RDMA and low latency features. This includes reliable connected service, datagram service, RDMA and send/receive semantics, atomic operations, user level multicast, user level I/O access, kernel bypass, and zero copy.
5. The OFA verbs used by ConnectX-2 EN with RoE are based on InfiniBand and have been proven in large scale deployments and with multiple ISV applications, both in the HPC and EDC sectors. Such applications can now be seamlessly offered over ConnectX-2 EN with RoE without any porting effort required
6. ConnectX-2 EN with RoE based network management is the same as that for any Ethernet and DCB-based network management, eliminating the need for IT managers to learn new technologies.



350 Oakmead Parkway
Sunnyvale, CA 94085

Tel: 408-970-3400 • Fax: 408-970-3403

www.mellanox.com

© Copyright 2010, Mellanox Technologies. All rights reserved. Preliminary information. Subject to change without notice. Mellanox, BridgeX, ConnectX, InfiniBlast, InfiniBridge, InfiniHost, InfiniRISC, InfiniScale, InfiniPCI, and Virtual Protocol Interconnect are registered trademarks of Mellanox Technologies, Ltd. CORE-Direct, FabricT, and PhyX are trademarks of Mellanox Technologies, Ltd. All other trademarks are property of their respective owners.